







Crystal White




we like good service


Luxura X_s stands for easy service and maintenance that can be carried out by any employee.

- Easy replacement of tubes or high pressure lamps
- Easy cleaning
- Easy refilling of Xsens cartridges and Qsens reservoir
- Easy emptying of airco reservoir
- Easy cleaning or changing of dust filters





BPS/HPS





Connect line: An optional Ambient FlowLight element that connects the bench and canopy



Front Panel standard



Centre line: An optional Ambient FlowLight element that runs in the centre of canopy



Front Panel with Brandshield and Ambient FlowLight (standard for $\rm X_5$ 38 SLi)



Luxura X ₅	34 SLi	34 SLi Intensive	34 SLi High Intensive	34 SPr	34 SLI BALANCE
Tubes top	18 x 100 W	18 x 160 W	18 x 160 W	18 x 120 W	18 x 180 W Premium Balanced E-Power
Tubes base	16 x 120 W XL	16 x 120 W XL	16 x 180 W XL	16 x 120 W XL	16 x 200 W XL Premium Balanced E-Power
Face tanner	3 x 400 W	3 x 400 W	3 x 400 W	14 x 25 W	3 x 400 W
Central air exhaust capacity (top)	2000 m ³				
Connection	400V/3N~/50Hz	400V/3N~/50Hz	400V/3N~/50Hz	400V/3N~/50Hz	400V/3N~/50Hz
Power (with AirCo)	6 kW (7,3 kW)	7,1 kW (8,3 kW)	8,1 kW (9,4 kW)	4,8 kW (5,9 kW)	9 kW (10,2 kW)
Fuses (with AirCo)	3 x 11 A (3 x 16 A)	3 x 13 A (3 x 17 A)	3 x 15 A (3 x 19 A)	3 x 10 A (3 x 13 A)	3 x 16 A
Weight	365 kg (AirCo + 40 kg)	380 kg (AirCo + 40 kg)	395 kg (AirCo + 40 kg)	365 kg (AirCo + 40 kg)	380 kg (AirCo + 50 kg)

Technical modifications reserved.

























standard

BPS (not for 34 SPr)

Adjustable face tanners (0-1-2-3)

XL light in bench

Full colour display

Smart touch control

8 steps adjustable body cooler

8 steps adjustable face cooler

Dust filters

Smart cooling

EasyLift acrylic system bench

Front Panel Easy Move

Quickstart

Programmable internal timer

Connection for external timer

SoundAround Plus²

Loudspeakers

1 hour counter non-resetable

2 hour counters resetable

optional

Ambient FlowLight for Centre line

Ambient FlowLight for Connect line 1

Luxury Front Panel with Brandshield and

Ambient FlowLight 1

HPS (not for 34 SPr)

ContourPlus (standard feature for 34 SLi

High Intensive)

Xsens I

Xsens III

Qsens

AirCo³

Pre-wiring⁴

Air extraction adapter

(2 x 180mm Ú 300mm)

Air extraction cover